

SPECIFICATIONS:

GENERAL

DEPTH	26-1/2 in. (67.3 cm.)
WIDTH	41-1/2 in. (105.4 cm.)
HEIGHT	53 in. (134.6 cm.)
SHIPPING WEIGHT (DOMESTIC)	365 lbs. (166 Kg.)
NET WEIGHT	355 lbs. (151.96 Kg.)
POWER REQUIREMENTS	120VAC, 60 Hz., 480 watts 5 amps. 220/240VAC, 50 Hz., 438 watts 2.5 amp.

RECORD CHANGER MECHANISM

CAPACITY	100 records
RECORD SIZE	7 inches
SPEED	45 RPM 33 and 45 RPM (with optional Automix)

CREDIT AND PRICING SYSTEM

ACCUMULATOR TYPE CREDIT SYSTEM – ONE AND FIVE DOLLAR BILLS OPTIONAL	
COINS ACCEPTED	Nickels Dimes Quarters Half-Dollars Dollar Coins
TOTAL CREDIT ACCUMULATIONS	.99
PRICING	See Pricing, Page 8

SOUND SYSTEM

CARTRIDGE

TYPE	Shure Dynetic Variable Reluctance
FREQUENCY RESPONSE	20 to 20,000 Hz.
CHANNEL SEPARATION	25 db @ 1,000 Hz.
NOMINAL COMPLIANCE	.20 x 10 ⁻⁶ cm/dyne
TRACKING FORCE	.3-4 grams
OUTPUT	7 mv.
STYLUS	1 mil. diamond

POWER AMPLIFIER

125 watt Stereo	
FTC Rating, 4 Ohm Loads @ 1% THD	144 watts RMS
FTC Rating, 70V Lines @ 1% THD	126 watts RMS

PREAMPLIFIER

AVC CONTROL RANGE	40 db
TREBLE CONTROL	12 db/octave 10,000 Hz. full 6,000 Hz. moderate 3,000 Hz. low
BASS CONTROL	Compensates for bass loss at low volume levels 12 db per octave.