

Zenith, cleaning, loading, filling

1. Check cup size, load cups
2. Remove canisters to fill
3. Remove contact surface items
4. Clean whipper stations
5. Remove whipper trays and waste buckets
6. Remove powder conveyors from the canisters
7. Remove sugar tube and sugar chute
8. Remove ES brewer unit and rinse, dry top
9. Remove fresh brewer and rinse components
10. Clean and soak all hygiene parts
11. Reassemble all parts
12. Remove cup station assembly, clean and replace
13. Empty waste buckets, clean base of machine,
Replace waste buckets
14. Test vend selections to ensure ingredient canisters
are primed and ready to vend

In addition to the routine above, on a weekly basis, the fresh brewer filter plate should be destained as detailed separately

*N & W recommend the use of a de-tannin liquid cleaner such as “ND 20”
We also recommend the use of a vend cleaning agent such as “Vendkleen”*

N&W Fresh brewer cleaning instruction

The following procedure should be carried out on a weekly basis, the procedures should be carried out more frequently for machines having above average drink throughput or if heavy tannin build up is experienced.

- 1. Remove the brewer extraction hood**
- 2. Remove the mixer bowl and diffuser insert**
- 3. Remove the brewer chamber feeding pipe from the cover**
- 4. Remove the brewer cover plate**
- 5. Remove the brewer chamber & piston by pulling the lever across to the right and pulling the chamber forward**
- 6. Separate the chamber and piston ready for cleaning**
- 7. Remove filter plate assembly by pressing the lever below the holder**
- 8. Remove the scraper by pulling forward and out from the brewer assy.**
- 9. Remove the gasket and filter from the filter plate assembly**
- 10. Soak the filter plate in de-tannin solution for the recommended time**
- 11. Soak the brewer chamber, piston and scraper in vend cleaning solution**
- 12. Replace the scraper, assemble the brew chamber and piston**
- 13. Replace the brewer chamber, push the lever to the right to relocate and push home the chamber**
- 14. Pull the chamber forward to make sure that it is located securely**
- 15. Rinse and replace the filter to the filter holder, lift the “T” bar to meet the holder, which should snap into place.**
- 16. Lift the filter plate assembly to check that it is in line with the chamber**
- 17. Make sure that the filter outlet pipe is running from the side not the front**
- 18. Refit the brewer cover plate**
- 19. Fit the mixer tube that runs from mix chamber to brewer**
- 20. Refit the mixing chamber to the mixer tube**
- 21. Make sure to fit the diffuser to the mixing bowl**
- 22. Refit the extraction hood**

*N & W recommend the use of a de-tannin liquid cleaner such as “ND 20”
We also recommend the use of a vend cleaning agent such as “Vendkleen”*